



Price List
USD
(PIMA)
2007

ISCO GROUP
INTERNATIONAL SECURITY COMPANIES CORP.
P.O.B. 3142 TEL AVIV
61031 ISRAEL
MAIL: INFO@ISCOGRP.COM
WEB: WWW.ISCOGRP.COM

P/N	Model	Description	Price
-----	-------	-------------	-------

CONTROL PANELS







HUNTER-PRO 32





8 to 32 zones intrusion alarm hybrid panel, integrated with various wireless devices, especially designed to answer advanced security needs for medium sized commercial and residential installations.

- ◆ Basic panel with 8 zones:
 - Expandable up to 16 local wired zones (EXP-PRO)
 - Expandable up to 32 wired zones with SecuBUS™ expanders (IO-8)
 - Up to 24 wireless zones and 24 keyfobs with fully bus integrated Visonic's wireless receiver (IO-W)
 - Any combination of the above expanders
- ◆ Full supervision of wireless detectors (life signal, low battery, fault)
- ◆ Double EOL Resistors
- ◆ Supports a wide range of partition options:
 - Up to 16 partitions each with own Account ID and Users
 - Up to 8 subsystems each with separate keypads, IDs, and Users
- ◆ Comprehensive Zone Tests for flawless installation: Walk Test, Soak Test, etc.
- ◆ Two options for viewing system status:
 - "PIMA" Style: Status of all 32 zones is displayed simultaneously
 - Detailed: Scrolling events, zones' and system's status
- ◆ Four Monitoring Stations phone numbers
- ◆ PIMA unique Integrated Digital Communicator (telephone, long-range radio and/or GSM)
- ◆ Supports split and double reporting to two monitoring stations with different account IDs
- ◆ LCD keypad with multilingual Menu-Driven screens for easy programming and operation
- ◆ Three alternatives for easy programming (Keypad, Fast Programmer, Local/Remote download software)
- ◆ Up to 24 users (4 to 6 digits codes) with various authorization levels
- ◆ Easy and user friendly operation & programming with single key functions
- ◆ Various accessories:
 - Built-in subscriber dialer (4 numbers) with optional Voice Unit (VU-20)
 - Remote listen-in accessory (MIC-200)
- ◆ Memory Log up to 410 events (100 non-volatile)
- ◆ Automatic Arming at a preset time (passive) and/or after a preset silence time (active)
- ◆ System remote control via any touchtone telephone










6240004	HUNTER-PRO PCB	PCBA only	85
4210016	HUNTER-PRO Box	Metal Box for HUNTER-PRO	17
1810002	Transformer	230Vac Transformer for PIMA control panels	12
3120004	Tamper	Tamper Switch for PIMA metal boxes	1.5
8340007	HUNTER-PRO Assembled-1	HUNTER-PRO in metal box with tamper (NO transformer) TO ORDER HUNTER-PRO 16Z USE P/N: 8340004	Call
8340005	HUNTER-PRO Assembled-2	HUNTER-PRO in metal box WITH tamper & transformer TO ORDER HUNTER-PRO 16Z USE P/N: 8340001	112

P/N	Model	Description	Price
6212004	EXP-PRO 	Eight (8) zone Expansion card for HUNTER-PRO (Rev E)	32
6237001	I/O-8 PCB 	Addressable expansion card connected via the keypads bus (SecuBUS™). PCB Assembled Only ◆ 8 input zones and one relay output. ◆ Tamper protected via the SecuBUS™ communication	51
8500006	I/O-8 Assembled 	I/O-8 assembled in a heavy-duty Polycarbonate case Ready for installation	61
8500005 8500004	I/O-W 433 I/O-W 868 	Integrated Wireless Receiver ◆ Performs with Visonic wireless devices ◆ Connects via the SecuBUS™ communication ◆ Working frequency: 433/868Hz ◆ Supports 24 devices + 24 keyfobs	99
8330001	OUT-1000 	Eight (8) open collector Outputs card for HUNTER-PRO Current capability: 200mA	59
8490001	COMMAND-48	A 48 zone remote annunciation, used to drive a graphic display (e.g., Mimic Panel) or remote points readout (e.g., emergency call center). The unit drives indication LEDs that display zone status: open, closed, alarmed and bypassed.	114
8450001	Mimic Panel 	A custom made Mimic Panel according to customer's own drawing and requirements. Drawings can be hand made or computer graphic files. Includes: Command-48, Mimic Panel design and build, Casing and Wiring.	Call







Notes: ◆ For "Keypads" see page 7
◆ For "Wireless Devices" see "Visonic Vendor Price List" on page 16
◆ For "Transmitters (RF & GSM) and Antennas" see page 8








<p>CAPTAIN-i</p>  <p>Cost-effective 6 zones intrusion alarm panel, especially designed for small business and residential installations.</p> <ul style="list-style-type: none"> ◆ PIMA unique Integrated Digital Communicator (telephone, long-range radio and/or GSM) ◆ Built-in subscriber dialer with optional Voice Unit (VU-20) ◆ Supports 2 partitions <ul style="list-style-type: none"> ○ Each zone can be assigned to either or both partitions ○ Each user can be assigned to either or both partitions ◆ Double EOL Resistors ◆ Remote and local software download ◆ 4 to 6 digits codes: primary code; short code; 8 user codes, duress code ◆ Remote listen-in accessory (MIC-200) ◆ Memory log of events ◆ Wireless detection and remote control with PIMA's wireless ad-on receiver (RC-U) 			
6202003	CAPTAIN-i PCB	PCB only	61
4210005	CAPTAIN-i BOX	Metal Box for CAPTAIN-i	21
1810002	Transformer	230Vac Transformer for PIMA control panels	14
3120004	Tamper	Tamper Switch for PIMA metal boxes	1.5
8120009	CAPTAIN-i Assembled-1	CAPTAIN-i in metal box (NO transformer)	Call
8120005	CAPTAIN-i Assembled-2	CAPTAIN-i in metal box WITH transformer	87


Notes: ◆ For "Keypads" see page 7
◆ For "Wireless Add-On Systems" see "Visonic Vendor Price List" on page 16
◆ For "Transmitters (RF & GSM) and Antennas" see page 8











P/N	Model		Description	Price
KEYPADS				
8410019	RXN-400		Stylish illuminated LCD <ul style="list-style-type: none"> ◆ Keypad display supports most languages (per system software) ◆ 32 character LCD display ◆ Supports PIMA SecuBUS™ (supervised keypad bus) 	87
8410024	RXN-410		Stylish LARGE illuminated alpha numeric LCD <ul style="list-style-type: none"> ◆ Keypad display supports most languages (per system software) ◆ 32 character LCD display ◆ Supports PIMA SecuBUS™ 	98
8410062	Technician Keypad		Special alpha numeric LCD keypad <ul style="list-style-type: none"> ◆ Keypad display supports most languages (per system software) ◆ 32 character LCD display for easy programming ◆ Supports PIMA SecuBUS™ ◆ Connects to panel, LED keypad and/or BUS 	67
8410005	RX-406		6 LEDs zone display + Arm and Fault LEDs <ul style="list-style-type: none"> ◆ 5 status LEDs 	28
8410050	RXN-416		16 LEDs zone display + Arm and Fault LEDs <ul style="list-style-type: none"> ◆ 5 status LEDs ◆ Supports PIMA SecuBUS™ ◆ FOR HUNTER-PRO 32 CONTROL PANEL (VER 3.1 & UP) 	33
8310008	RX-6		6 LEDs zone/status display + Arm, Bypass and Fault LEDs <ul style="list-style-type: none"> ◆ Quick Reference Guide (QRG) on keypad door 	24
8310009	RXN-9		9 LEDs zone/status display + Arm, Bypass and Fault LEDs <ul style="list-style-type: none"> ◆ Quick Reference Guide (QRG) on keypad door ◆ Supports PIMA SecuBUS™ ◆ FOR HUNTER-PRO 32 CONTROL PANEL (VER 3.8 & UP) 	30
8380002	RXN-200		Outdoor Anti-Vandal keypad <ul style="list-style-type: none"> ◆ IP-96 compliant ◆ 3 LED indicators ◆ Water and dust proof ◆ Used for Arm/Disarm and Access Control 	163
8180006	VKD-1		Virtual Keypad is a software & hardware package to remotely control PIMA control panels. VKD-1 acts as a standard PIMA LCD keypad by connecting the panel to a PC locally and/or remotely via the Internet.	71.40





Notes:

P/N	Model	Description	Price
TRANSMITTERS (RF & GSM) AND ANTENNAS			
GSM Cellular Transmitters			
8300012	GSM-100/1800 	Multi-Protocol, Full-Data, GSM Alarm Events Transmitter, for PSTN Backup and as a Primary Communicator DUAL-BAND GSM 900 / 1800 MHZ	Call
8300013	GSM-100/1900 	Multi-Protocol, Full-Data, GSM Alarm Events Transmitter, for PSTN Backup and as a Primary Communicator SINGLE-BAND GSM 1900 MHZ	Call
VHF Radio Transmitters			
8200010 8200011	TRV-100DP H TRV-100DP L 	Digital VHF long-range radio transmitter High/Low frequencies HIGH: 154 TO 174 MHZ LOW: 136 TO 156 MHZ	140
UHF Radio Transmitters			
8300006 8300009 8300005	TRU-100DP H TRU-100DP M TRU-100DP L 	Digital UHF long-range radio transmitter High/Medium/Low frequencies HIGH: 470 TO 500 MHZ MEDIUM: 435 TO 470 MHZ LOW: 400 TO 435 MHZ	181
Stand-Alone Radio Transmitters			
8390001	SAT-8 	Stand-Alone Controller/Decoder with 8 inputs for VHF/UHF long-range radio transmitter TRANSMITTERS ARE NOT INCLUDED AND NEED TO BE SPECIFIED AND ORDERED SEPARATELY ! AVAILABLE TRANSMITTERS: TRV-100DP H/L (FOR VHF) TRU-100DP H/M/L (FOR UHF)	call
8391001	SAT-9 	Stand-Alone Controller/Decoder for VHF/UHF long-range radio Transmitter with PSTN line interface: ◆ Backup for a PSTN dialer or main communicator ◆ Designated Phone # (for line interception) ◆ Supports variety of protocols ◆ Accounts from panel or internally programmed ◆ Supports two frequencies (different protocol per frequency) TRANSMITTERS ARE NOT INCLUDED AND NEED TO BE SPECIFIED AND ORDERED SEPARATELY ! AVAILABLE TRANSMITTERS: TRV-100DP H/L (FOR VHF) TRU-100DP H/M/L (FOR UHF)	call


P/N	Model	Description	Price
GSM Antennas			
6110006	CP-101	 1.5DB 870 TO 960 / 1710 TO 1800 MHz	call
6110012	CP-102	 1.5DB 1900 MHz	call
6110009	CPM-17	 3DB 900 / 1800 / 1900 MHz including Magnet Base ANTENNA REFLECTOR (P/N 4210033)	call
6110010	CP-1881	 5DB 824 TO 960 / 1800 MHz for Wall mount	call
6110011	CP-1882	 7DB 860 TO 960 / 1800 MHz for Wall mount	call
4210033	Antenna Reflector Plate	 General-purpose antenna reflector mounting plate. Can be used as a base to any transmitter/receiver antenna (e.g., TRV/TRU-100, SAT-8, RC-U wireless receiver, GSM-100, etc.)	call
VHF/UHF Antennas			
6110003	Antenna-VHF	VHF antenna for PIMA transmitters	
6110004	Antenna-UHF	UHF antenna for PIMA transmitters	
5240023 5240026 5240020	Metal Antenna Reflector for VHF transmitters	 External VHF antenna reflector with: Reflector with 3 meters RG-58 cable Reflector with 6 meters RG-58 cable Reflector with 10 meters RG-58 cable VHF ANTENNA IS NOT INCLUDED !	Call
5240013 5240016 5240010	Metal Antenna Reflector for UHF transmitters	External UHF antenna reflector with: Reflector with 3 meters RG-58 cable Reflector with 6 meters RG-58 cable Reflector with 10 meters RG-58 cable UHF ANTENNA IS NOT INCLUDED !	Call

P/N	Model	Description	Price
WIRELESS ADD-ON SYSTEMS			
Integrated System			
8500005 8500004	I/O-W 433 I/O-W 868 	Integrated Wireless Receiver ◆ Performs with Visonic wireless devices ◆ Connects via the SecuBUS™ communication ◆ Working frequency: 433/868Hz ◆ Supports 24 devices + 24 keyfobs	100
	VISONIC Wireless Devices	For Visonic Wireless devices see the "PIMA VISONIC VENDOR PRICE LIST"	
Stand-Alone Add-on System			
	VISONIC Stand-Alone Wireless Receivers	For Visonic Wireless devices see the "PIMA VISONIC VENDOR PRICE LIST"	
Notes: Batteries Included with all devices.			


P/N	Model	Description	Price
ACCESSORIES			
Installation Accessories			
8180005	LCL-11A	 <p>Serial Interface adapter. Used as follows:</p> <ul style="list-style-type: none"> ◆ PC interface for local Download to a control panel with COMAX and LCD keypad; Use TC-3 to connect LCD keypad to customers' LED keypad ◆ Serial (RS-232) interface (connected to the panels' serial port) for serial printer or "Smart Home" applications 	72
5200010	Modem	 <p>External modem, 56.6 kbps to be used with COMAX Upload/Download application</p>	73
8220002	PRG-22	 <p>Fast programmer for storing control panel parameters Can ONLY be connected to LCD keypad; Use TC-3 and LCD keypad where customer has an LED keypad.</p> <ul style="list-style-type: none"> ◆ CAPTAIN-i (4 programs) ◆ HUNTER-PRO 32 (1 program) <p>Note: The PRG-22 requires DPR-33 for programming with the COMAX software.</p>	51
8420002	DPR-33	 <p>Adapter for programming PRG-22 with PC and COMAX</p>	33
8420001	DPR-44	 <p>Adapter for programming Transmitters and SAT-8 with PC and COMAX</p>	33
3411007	TC-3	 <p>Technician Cable for connecting any PIMA LCD keypad to customers' LED keypad. Alternately, connects to the control panel's keypad port or terminal block.</p>	11
Power Supplies & Batteries			
8290002	PS-2	 <p>Controlled Power supply 1.2 Amp, 12V in metal box The PS-2 is controlled by a microchip and has two outputs to the Control Panel that can be remotely monitored:</p> <ul style="list-style-type: none"> ◆ Battery fault ◆ Mains fault 	71
5230004	TP12-5	 <p>Lead Acid battery 12V, 5 AH/20 hrs</p>	12
5230009	TP12-7.5	 <p>Lead Acid battery 12V, 7 AH/20 hrs</p>	19
8370001	BTS-1	 <p>Battery Splitter wire For use with a high current devices (e.g., siren, relay)</p>	5

P/N	Model		Description	Price
Panel Accessories				
8150001	REL-1		Relay board Power supply: 12VDC Contact rating: 10A @ 120VAC/24VDC	6
8320001	SP-01		Surge Protector for a telephone line from lightning damage	19
8440001	ADSL-01		ADSL filter for a telephone line interface where a broadband internet service is shared with the telephone line	Call
5100003	VU-20		Synthesized Recordable Voice Message box for PIMA control panels	26
8210002	MIC-200		Amplified Microphone module ◆ Remote listen-in with PIMA control panels ◆ New esthetic design	69

VARIOUS DETECTORS & SENSORS

5400014	DEFENDER-PRO		Microprocessor-controlled PIR detector ◆ Free of vertical adjustment ◆ High-detection sensitivity: 0.5 to 12 meters ◆ True Motion Recognition™ algorithm (patented) ◆ 3D multiple curtain coverage with no dead zones ◆ Temperature compensation ◆ White light & UV protection ◆ Remote walk test 10 UNITS PER BOX (PRICE IS IS FOR A SINGLE DETECTOR)	12
5000007	BR-1		Wall mount bracket for DEFENDER-PRO PIR	4
5000008	BR-2		Corner mount bracket for DEFENDER-PRO PIR	6
5000009	BR-3		Ceiling mount bracket for DEFENDER-PRO PIR	7

DIGITAL ACCESS KEYPADS

5330001	DK-10		Self contained Digital keypad (up to 120 user codes)	34
5330002	DK-30C		Digital keypad for high security-split modules	62
5330003	DK-80C		As DK-30C but with internal siren	67

P/N	Model	Description	Price
-----	-------	-------------	-------

SENTINEL MONITORING STATION RECEIVER & REPEATER

Combined with a unique driver (MCARD™) and software (Andromeda) creates a cost-effective Central Monitoring Station (CMS) The same PC card with a different driver can be installed as a "Smart" Repeater System

SENTINEL hardware contains a maximum of 2 Radio channels and 4 Telephone lines Smart Decoder

SENTINEL hardware supports a maximum of 8000 (!) subscribers

The MCARD™ driver enables the different features of the SENTINEL hardware and can be ordered in different configuration combinations:

Central Station	-OR-	Smart Repeater
1/2 Radio Channels	-AND/OR-	1/2/3/4 Telephone lines
PAF™ only format	-AND/OR-	PAF™ + Other formats
250/500 Subscribers	-OR-	Unlimited (8000) Subscribers



SENTINEL Unlimited

	Model	Subscribers	Description	Price
8086001	CMS/RMS-2000	UNLIMITED	TWO TELEPHONE LINES / PAF™ only ⁽¹⁾	Call
8086002	CMS-0010	UNLIMITED	RECEIVER 1 st RADIO CHANNEL / PAF™ only ⁽¹⁾	Call
8086003	RMS-0010	UNLIMITED	REPEATER 1 st RADIO CHANNEL / PAF™ only ⁽¹⁾	Call

Note: 1. Minimum SENTINEL UNLIMITED order includes: two telephone lines OR one radio channel

SENTINEL Junior

	Model	Subscribers	Description	Price
8086014	CMS-2100J5	500	TWO TELEPHONE LINES / PAF™ + Other formats ⁽²⁾	Call
8086015	CMS-0010J2.5	250	RECEIVER SINGLE RADIO CHANNEL / PAF™ only	Call
8086016	CMS-0010J5	500	RECEIVER SINGLE RADIO CHANNEL / PAF™ only	Call

Note: 2. Minimum SENTINEL JUNIOR order includes: two telephone lines with other formats OR single radio channel PAF™ only

SENTINEL Add To

8086004	CMS/RMS-1000	ADDITIONAL TELEPHONE LINE / PAF™ only ⁽³⁾	Call
8086005	CMS/RMS-0100	ADDITIONAL FORMAT for 1 Telephone line	Call
8086006	CMS/RMS-00A0	ADDITIONAL RADIO CHANNEL / PAF™ only ⁽⁴⁾	Call
8086007	CMS/RMS-0001	ADDITIONAL FORMAT for 1 Radio channel	Call
3411046	CRD-T	Standard telephone cord for PCI card (RJ11 x RJ11)	Call
3411041	CRD-R	Radio connection cable for PCI card	Call








Notes:









3. Adding the additional telephone line does not add to the total number of subscribers that remains 250 or 500 as the system version
4. Can be applied only as a second radio channel!
5. Each telephone line requires a separate phone cord; both radio channels use a single D type connector. The required cords and cable are included with the product, e.g. CMS-2100 includes 2 telephone cords
6. When ordering an upgrade (i.e., additional line/channel) it also includes the required telephone cord/cable for connecting the additional telephone/radio input






SOFTWARE

4710002	ANDROMEDA-W	Central Monitoring Station Management software for Windows	Call
4710001	COMAX	Local & remote Upload/Download software for programming PIMA's control panels and transmitters	Call

OTHER VENDOR ACCESSORIES PRICE LIST			
P/N	Model	Description	Price
Active IR Detectors			
5060016 5060020	IR-2000 Black IR-2000 White	 Micro Active Twin Infrared Beam detector for 24 hours periferial protection For 10 meters range Supply:12~24Vdc/ac; Response Time: 100mS; Alarm Output: N.C./N.O. 1A@120Vac; 10 SETS PER PACKAGE (PRICE IS FOR 1 SET !)	25 Call
5060019 5060015 5060012 5060006 5060007 5060008 5060009 5060010	PROTECTOR-10 PROTECTOR-15 PROTECTOR-20 PROTECTOR-30 PROTECTOR-40 PROTECTOR-60 PROTECTOR-80 PROTECTOR-120	 Active Infrared Twin Beam detector for 24 hours periferial protection: WHITE For 10 meters range For 15 meters range (smaller in size) For 20 meters range For 30 meters range For 40 meters range with Laser adjustment For 60 meters range with Laser adjustment For 80 meters range with Laser adjustment For 120 meters range with Laser adjustment All models Supply:10~30Vdc; Response Time: 50~700mS; Alarm Output: N.C./N.O. 1A@120Vac; Alignment: Horizontal ±90° & Vertical ±15°	Call 40 40 56 64 67 70 105
5010044 5010051 5010045 5010052 5010046 5010053 5010047 5010054	PROTECTOR-2X PROTECTOR-2XW PROTECTOR-4X PROTECTOR-4XW PROTECTOR-6X PROTECTOR-6XW PROTECTOR-8X PROTECTOR-8XW	 Active Infrared Barrier (Curtain) detectors set for 24 hours periferial protection: With 2 beams – Black With 2 beams - White With 4 beams – Black With 4 beams - White With 6 beams – Black With 6 beams - White With 8 beams – Black With 8 beams – White All models Range: 8 meters; Supply:10~30Vdc; Response Time: immediate when 2 beams are crossed, otherwise 2 Sec; Alarm Output: N.C./N.O. 1A@120Vac	62 62 85 85 105 105 115 115
PIR Detectors			
5010022	3D	 Double Sensor Anti-Mask PIR Range: 16 meters Angle: 120 degrees Alarm Output: N.C. 0.1A @ 24 Vdc Max Mask Relay: N.C. 0.1A @ 24 Vdc Max 10 UNITS PER PACKAGE (PRICE IS FOR 1 UNIT!)	39
5010029	MR-CRT	 Curtain Protection PIR detector Range: 8 meters Angle: 90 degrees Alarm Output: N.C. 0.1A @ 28Vdc 10 UNITS PER PACKAGE (PRICE IS FOR 1 UNIT!)	26
5080002	TLC-360	 Ceiling-mount PIR detector Range: 10 meters Angle: 360 degrees Response Time: 0.5~1.5 mSec	23

P/N	Model	Description	Price
Reed Switch Detectors			
5040001	MS-11S	 Surface mount mini magnetic contact with wire Contact rating: N.C. SPST 0.5A @ 200 Vdc / 10W Color: Ivory	15
5040002	MS-24ST	 Surface mount magnetic contact with screws Contact rating: N.C. SPST 0.5A @ 200 Vdc / 10W Color: Ivory 10 UNITS PER PACKAGE (PRICE IS FOR 10 UNITS!)	13
5040007	MC-04B		63
5040008	MC-04W		
5040010	MC-03W	 Concealed Magnetic Contact with wire for metal doors & frames Contact rating: N.C. SPST 0.5A@100VDC Color: White 50 UNITS PER PACKAGE (PRICE IS FOR 50 UNITS!)	63
Shock and Glass Break Detectors			
5050002	GBD-II	 Shock and Glass break detector Power Input: 9-16 Vdc Detection Range: 10 meters Alarm Output Relay: NC 50mA @ 24 Vdc 10 UNITS PER PACKAGE (PRICE IS FOR 1 UNIT!)	15
5060005	VB-3	 Stylish and easy to install Shock Sensor ABS with tightly 24K gold copper material Adjustable sensitivity (0.5 – 50 mSec) 10 UNITS PER PACKAGE (PRICE IS FOR 1 UNIT!)	6
Fire and Smoke Detectors			
5020001	APOLLO	 Ionization Smoke detector Operating voltage: 12 Vdc	28
5000002	BR-A	 Mounting Bracket for the APOLLO smoke detector 10 UNITS PER PACKAGE (PRICE IS FOR 1 UNIT!)	4

P/N	Model		Description	Price
Sirens				
5220001	SIR-01		Internal Siren Power Rating: 15W Frequency: 400-9000Hz Voltage: 9 Vdc 60 UNITS PER PACKAGE (PRICE IS FOR 1 UNIT!)	3
5220002	SIR-02		External Siren 8 ohms, 15 watts Frequency: 400-9000 Hz 24 UNITS PER PACKAGE (PRICE IS FOR 1 UNIT!)	5
5220012 5220014	WP-06 (RED) WP-06 (ORANGE)		Outdoor Siren Size:210L x 130W x 78H mm Operating Voltage: 6 - 15 Vdc Rated Voltage: 12 Vdc Rated Power: 150W SPL DP/1M: 112±3 Len Color: Red/Orange 24 UNITS PER PACKAGE (PRICE IS FOR 1 UNIT!)	10
5220015	WP-12 (RED)		Indoor Red Siren with Strobe Operating Voltage: 12 Vdc / 150mA Sound: 1 Tone Sound Level: 105 dB 100 UNITS PER PACKAGE (PRICE IS FOR 1 UNIT!)	6
5220016 5220017	WP-18 (RED) WP-18 (ORANGE)		Outdoor Siren Operating Voltage: 6 - 15 Vdc Rated Voltage: 12 Vdc Sound Level: 115 dB Len Color: Red/Orange 20 UNITS PER PACKAGE (PRICE IS FOR 1 UNIT!)	18
5220020	WP-12W		Indoor Piezo Siren in wight box Operating Voltage: 12 Vdc / 150mA Sound: 1 Tone Sound Level: 105 dB 100 UNITS PER PACKAGE (PRICE IS FOR 1 UNIT!)	4
5220021	WP-09		Square Piezo Siren Rated Voltage: 6-12 Vdc / 10W Sound: 1 Tone Sound Level: 105 dB	3
5260003	ML-03 (RED)		Warning Strobe flasher Operating Voltage: 12 Vdc / 120mA 100 UNITS PER PACKAGE (PRICE IS FOR 1 UNIT!)	5

P/N	Model	Description	Price
General Accessories			
5250002	MO-1	 <p>Emergency Panic button N.O. push to close S.P.S.T</p> <p>20 UNITS PER PACKAGE (PRICE IS FOR 1 UNIT!)</p>	3
5270005	ACS-102	 <p>Wireless 2 channel receiver including 2 X Dual channel Push Button transmitters (E102)</p> <p>Power Supply: 8.2-16 Vdc Range: 200 meters in open space Frequency: 433.92 MHz</p> <p>10 UNITS PER PACKAGE (PRICE IS FOR 1 UNIT!)</p>	36
5280010	E102	 <p>Dual channel Push Button transmitter</p>	10
3110001	KEY-01	 <p>On-off Key Switch Contact Rating: 2A, 250 Vac</p>	6
3110002	KEY-02	 <p>Spring return on-off Switch Contact Rating: 2 A, 250 Vac</p>	10